

ALTEC WRAPPED BALE GRABS

M10P120 The best seller

More than 16,000 units in service throughout Europe



ON FRONTLOADER



ON TELESCOPIC LOADER



ON COMPACT LOADER



GRABS WITH
0.70 TO 1 M
LIFT HEIGHT



M10SP



MA150P
Lift height +1.60m



MA400P
Lift height +3.80 m

INDEPENDENT SYSTEMS DIRECTLY ON TRACTOR

- The MA150P model grasps the bale in any position and stores it in two rows
- The MA300P – MA400P models also pick up the bale in any position and like all the ALTEC grabs, can be used for hay, straw or flax.
- The MA410P model is designed to work with bales weighing up to 1000 kg



... winning kinematics

Both hands grasp the bale and draw it to the middle of the chassis

With Altec grabs, wrapped bale handling is fast, safe and leaves the plastic film untouched.

● TIRELESS

The very large rotation axes of the hands stay straight and rigid. They also have anti-friction metal bushes and grease nipples.

● AGILE

Both hands are hinged. It's easy to and fast to pick up and deposit bales on right and left. The hands stay mobile even when the ram lets the bale go.



● STRONG

The rotation shafts are offset to the front so that the large lever arm situated between the axis of rotation and the ram shaft causes strong clamping. The ram operates by pushing and maximum clamping is obtained.



Multipurpose

Suitable for hay, straw or flax ... also capable of picking up large square bales – length 1.40 to 1.80 m



For every bale diameter up to 1.80 m



M10P120 - M10P160 - M10P180

● POWERFUL AND STRONG

The hands are strengthened to resist the power of the ram. The hands are of curved round, fine and smooth (inside and outside) tubing so as never to damage the bales.

● UNDEFORMABLE

The enclosed chassis will resist the high pressure of the ram and the weight of the bales

ON LIFTING RAMP



M10PR

ON TRADITIONAL LOADER



M10PS



Roller grabs for round bales

- M10R: on all telescopic and front loader, also for 3-point rear mounting
- Bale pickup and deposit in the same direction
- The 2 rotating rollers do not damage the bale
- Can be used without rollers 2 straight dia.40 tines
- Needs double acting supply
- Working capacity: 1100kg