

H&S

V-RAKES CR8 - CR10 - CR12



SPECIFICATIONS

	CR8	CR10	CR12
NUMBER OF RAKE WHEELS	8	10	12
WHEEL DIAMETER	55"	55"	55"
TEETH PER WHEEL	40	40	40
TOOTH DIAMETER	7mm	7mm	7mm
TRANSPORT WIDTH	8'6"	9'6"	9'6"
TRANSPORT LENGTH	13'	15'6"	18'
WINDROW WIDTH ADJUSTMENT	3'-5'	4'-6'	4'-6'
RAKING WIDTH	15'-19' 3 settings	18'-22' 3 settings	20'-24' 3 settings
RAKING WHEEL HUBS	Tapered Bearings	Tapered Bearings	Tapered Bearings
WING FLEX	Limited	Limited	Limited
2ND HOSE KIT	Optional	Optional	Optional
HITCH JACK	Standard	Standard	Standard
CENTER KICKER WHEEL	N/A	Optional	Optional
TRANSPORT WHEELS	2 - ST175/80D13	2 - ST175/80D13	2 - ST175/80D13
WEIGHT	1125 lbs	1275 lbs.	1440 lbs.

H & S V-Rakes have the flexibility to rake with one side only



Using the hitch jack, the operator can adjust the windrow width.



A single acting cylinder coupled with a simple linkage system allows for easy raising and lowering of rake wings.



Raking width on the H&S V-Rakes can be adjusted to 3 different positions with the pin and fine tuned by adjusting the turnbuckle screw.




The operator can adjust the fine tune spring to allow proper rake wheel down pressure.



H&S V-Rake in transport position.

Warranty: See operators manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation. Printed in U.S.A.



Manufactured in U.S.A.


Buy the **BEST**
BUY **H&S**

Models and specifications are subject to change without prior notice.

4/08 5M

H & S MANUFACTURING CO. INC.

2608 S. Hume Avenue
P.O. Box 768 • Telephone (715) 387-3414
FAX (715) 384-5463 • Website www.hsmfgco.com
MARSHFIELD, WI 54449



H&S WAREHOUSE 10145 Lakeshore Road
P.O. Box 1260 • Telephone (716) 736-7595
FAX (716) 736-7596 • Website www.hsmfgco.com
RIPLEY, NY 14775